



3 SERIES

HP Core

or Solid Core

10-32 Thread

3" Bend Radii (HP)

6" Bend Radii

(Solid Core)

- Temperature Range:
 -65 to +225°F / -54 to +107°C Std.
 -65 to +300°F / -54 to +149°C HEFT 2
- Low Backlash
- High Efficiency
- Conduit Color:
 Dark Maroon – HP Cable Std.
 Satin Black – HEFT 2

Specifications

Travel Inch/(mm)	Bulkhead End		Clamp End		Operating Loads	
	DIM "A" Inch/(mm)	DIM "B" Inch/(mm)	DIM "C" Inch/(mm)	DIM "D" Inch/(mm)	Push Lbs./(N)	Pull Lbs./(N)
1.0 (25.4)	3.00 (76.2)	4.44 (112.8)	2.31 (58.7)	3.75 (95.3)	80 (356)	120 (534)
2.0 (50.8)	4.00 (101.6)	5.94 (150.9)	3.31 (84.1)	5.25 (133.4)	80 (356)	120 (534)
3.0 (76.2)	5.00 (127.0)	7.44 (189.0)	4.31 (109.5)	6.75 (171.5)	70 (311)	120 (534)
4.0 (101.6)	6.00 (152.4)	8.94 (227.1)	5.31 (134.9)	8.25 (209.6)	60 (267)	120 (534)
5.0 (127.0)	7.00 (177.8)	10.44 (265.2)	6.31 (160.3)	9.75 (247.7)	45 (200)	120 (534)
6.0 (152.4)	8.00 (203.2)	11.94 (303.3)	7.31 (185.6)	11.25 (285.7)	35 (155.8)	120 (534)
7.0 (177.8)	9.00 (228.6)	13.44 (341.4)	8.31 (211.0)	12.75 (323.8)	25 (111.3)	120 (534)