



6 SERIES

HP Core

5/16-24 Thread

7" Bend Radii

- HP core (HP)
- Rod thread M8 (or 5/16-24 UNF)
- 178 mm (7") bend radii
- Low backlash
- High efficiency
- Temperature Range:
 - 54 - +107°C Std.
 - 54 - +149°C HEFT2

Specifications

Travel	Bulkhead End		Clamp End		Operating Loads	
Inch/(mm)	DIM "A" Inch/(mm)	DIM "B" Inch/(mm)	DIM "C" Inch/(mm)	DIM "D" Inch/(mm)	Push Lbs./(N)	Pull Lbs./(N)
1.0 (25.4)	3.25 (82.6)	5.00 (127.0)	2.56 (65.0)	4.31 (109.5)	250 (1112)	400 (1779)
2.0 (50.8)	4.25 (108.0)	6.50 (165.1)	3.56 (90.4)	5.81 (147.6)	250 (1112)	400 (1779)
3.0 (76.2)	5.25 (133.4)	8.00 (203.2)	4.56 (115.8)	7.31 (185.7)	210 (934)	400 (1779)
4.0 (101.6)	6.25 (158.8)	9.50 (241.3)	5.56 (141.2)	8.81 (223.8)	170 (756)	400 (1779)
5.0 (127.0)	7.25 (184.2)	11.00 (279.4)	6.56 (166.6)	10.31 (261.9)	130 (578)	400 (1779)
6.0 (152.4)	8.25 (209.6)	12.50 (317.5)	7.56 (192.0)	11.81 (299.9)	90 (400.5)	400 (1779)
7.0 (177.8)	9.25 (235)	14.00 (355.6)	8.56 (217.4)	13.31 (338.0)	60 (267)	400 (1779)