



## 8 SERIES

Armor Core

10" Bend Radii

3/8-24 Thread Standard

M10 Thread Upon Request

- Armor core
- Rod thread 3/8"-24 UNF
- 254 mm (10") bend radii
- Low backlash

- Temperature Range:  
-54 - +107°C Std.

## Specifications

Travel Inch/(mm)	Bulkhead End		Clamp End		Operating Loads	
	DIM "A" Inch/(mm)	DIM "B" Inch/(mm)	DIM "C" Inch/(mm)	DIM "D" Inch/(mm)	Push Lbs./(N)	Pull Lbs./(N)
1.0 (25.4)	3.69 (93.7)	5.56 (141.2)	3.19 (81.0)	5.06 (128.5)	700 (3114)	1000 (4448)
2.0 (50.8)	4.69 (119.1)	7.06 (179.3)	4.19 (106.4)	6.56 (166.6)	700 (3114)	1000 (4448)
3.0 (76.2)	5.69 (144.5)	8.56 (217.4)	5.19 (131.8)	8.06 (204.7)	600 (2669)	1000 (4448)
4.0 (101.6)	6.69 (169.9)	10.06 (255.5)	6.19 (157.2)	9.56 (242.8)	500 (2224)	1000 (4448)
5.0 (127.0)	7.69 (195.3)	11.56 (293.6)	7.19 (182.6)	11.06 (280.9)	400 (1779)	1000 (4448)
6.0 (152.4)	8.69 (220.7)	13.06 (331.7)	8.19 (208.0)	12.56 (319.0)	275 (1223.8)	1000 (4448)
7.0 (177.8)	9.69 (246.1)	14.56 (369.8)	9.19 (233.4)	14.06 (357.1)	150 (667.5)	1000 (4448)